

## K-SMOKE-42 Freestanding Smoker Cabinet



## PRODUCT FEATURES

- Freestanding gravity-fed charcoal smoker cabinet
- Includes hygenics and attractive solid-surface porcelain work top in either black or white
- Computer-controlled blower system for fool-proof temperature control
- 3 amps, 120V 60HZ, connect with standard outdoor electrical cord
- 490 pounds
- · Marine-grade stainless steel available

Overall Width / Installation Width	48.3 in (1226 mm)
Overall Depth / Installation Depth	32.63 in (830 mm)
Overall Height / Counter Height	41.2 in (1046 mm) / 35.3 in (895 mm) +/- 1 ¼ in (33 mm)
Approximate Product Weight	490 lb (222 kg)
Electrical Requirements	120VAC/60Hz Includes 1 ft. (30.5 cm) 3-prong grounded power cord.
Maximum AMP usage	3 amps
Main Burners Rating	Not available
Total BTUs	Not available

For outdoor use only. Do not build the smoker into a combustible enclosure. Maintain at least 6 inches (153 mm) of clearance between the sides and back of the smoker and any combustible surface, or use an insulating surround available from Kalamazoo. Never place the smoker underneath an overhead combustible structure or surface. Do not place the smoker in a location where it is likely to be exposed to a strong wind.

High altitude kit available.



## K-SMOKE-42 Freestanding Smoker Cabinet







