



810 WEST WASHINGTON BOULEVARD  
CHICAGO, IL 60607

8566 KRUM AVENUE  
GALESBURG, MI 49053

KALAMAZOOGOURMET.COM  
+1.800.868.1699

## K500HB Hybrid Fire Built-In Grill



### PRODUCT FEATURES


- 23" x 22" (506 square inches) of primary grilling surface
- Two cast bronze Dragon Burners™, 26,500 BTUs each (LP)
- Natural gas or bulk liquid propane
- Barbecue burner for indirect, low-temperature cooking
- Rotisserie system with infrared burner; motor mounted in cabinet; flip-up warming rack
- Safety valves for every burner and electronic control bezels with flame sensor LED indicators
- Kalamazoo's Advanced Cooking Concept with deep hopper cleaning
- Single Hybrid Fire Grilling System Drawer
- Stainless steel leveling legs (optional toe kick not shown)
- Laser-cut grilling surfaces with your choice of patterns optimized for cooking meat, fish, and vegetables
- Marine-grade stainless steel available

<b>Overall Width / Installation Width</b>	29.38 in (747 mm) / 28 in (712 mm)
<b>Overall Depth / Installation Depth</b>	32 in (814 mm) / 26.50 in (674 mm)
<b>Overall Height / Counter Height</b>	54.63 in (1388 mm) / 36 in (915 mm) +/- 1 ¼ in (33 mm)
<b>Approximate Product Weight</b>	360 lb (163 kg)
<b>Gas Requirements</b>	<b>Natural Gas:</b> 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick disconnect provided. Gas service line to deliver 7 i.w.c. at grill location. See BTU information below for pipe sizing.
	<b>Bulk Propane:</b> 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick disconnect provided. Gas service line to deliver 11 i.w.c. at grill location. See BTU information below for pipe sizing.
	<b>Propane Cylinder:</b> Not available
<b>Electrical Requirements</b>	120VAC/60Hz Includes 1 ft. (30.5 cm) 3-prong grounded power cord.
<b>Maximum AMP usage</b>	3 amps
<b>Main Burners Rating</b>	53,000 BTU liquid propane / 48,000 BTU natural gas
<b>Total BTUs</b>	69,500 BTU liquid propane / 64,500 BTU natural gas

Ensure proper gas pipe sizing. Diameter and length of the supply pipe may limit the pressure and BTU delivery.

For outdoor use only. Do not build the grill into a combustible enclosure. Maintain at least 6 inches (153 mm) of clearance between the sides and back of the grill and any combustible surface, or use an insulating surround available from Kalamazoo. Never place the grill underneath an overhead combustible structure or surface. Do not place the grill in a location where the rear hood openings are likely to be exposed to a strong wind.

High altitude kit available.



Do not place the grill in a location where the rear hood openings are likely to be exposed to strong wind. A wind break wall is recommended for installations where the prevailing wind may be a problem.

**WARNING:** This product can expose you to chemicals including nickel, which are known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warningsca.gov](http://www.P65Warningsca.gov)



810 WEST WASHINGTON BOULEVARD  
CHICAGO, IL 60607

8566 KRUM AVENUE  
GALESBURG, MI 49053

KALAMAZOOGOURMET.COM  
+1.800.868.1699

# K500HB Hybrid Fire Built-In Grill

