



PRODUCT FEATURES

- Wood-fired grill with motorized rotisserie spit that raises and lowers above the fire; motor mounted in cabinet
- 33" x 22" (726 square inches) of primary grilling surface
- Two powerful gas burners to start the wood fire, 24,000 BTUs each (LP)
- · Dual cooktop burners, 20,500 BTU each (LP)
- · Natural gas or bulk liquid propane
- · Electronic control bezels with flame sensor LED indicators
- · Deep hopper cleanout
- Right end cabinet for optional propane cylinder storage
- Optional laser-cut grilling surfaces available with your choice of patterns optimized for cooking meat, fish, and vegetables
- · Optional Argentinian-style V-grates with drippings trays
- · Marine-grade stainless steel available

Overall Width / Installation Width	86.38 in (2195 mm)
Overall Depth / Installation Depth	32.13 in (817 mm)
Overall Height / Counter Height	78.75 in (2000 mm) / 36 in (915 mm) +/- 1 ¼ in (33 mm)
Approximate Product Weight	700 lb (318 kg)
Gas Requirements	Natural Gas: 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick
	disconnect provided. Gas service line to deliver 7 i.w.c. at grill location. See BTU
	information below for pipe sizing.
	Bulk Propane: 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick discon-
	nect provided. Gas service line to deliver 11 i.w.c. at grill location. See BTU informa-
	tion below for pipe sizing.
	Propane Cylinder: 20 lb (9.1 kg) cylinder. 2 ft. (61 cm) gas hose with dual regulator
	provided.
Electrical Requirements	120VAC/60Hz Includes 1 ff. (30.5 cm) 3-prong grounded power cord.
	1.5 V "AAA" battery x 1 for cooktop burner ignition.
Maximum AMP usage	3 amps
Main Burners Rating	48,000 BTU liquid propane / 45,000 BTU natural gas
Total BTUs	89,000 BTU liquid propane / 83,000 BTU natural gas

Ensure proper gas pipe sizing. Diameter and length of the supply pipe may limit the pressure and BTU delivery.

This appliance is certified to the ANS Z21.58/CSA 1.6 (2018) standard for Outdoor Cooking Gas Appliances. As with all appliances certified to this standard, this appliance is for outdoor use only and may not be used underneath an overhead combustible structure or surface.

Do not build the grill into a combustible enclosure. Maintain at least 36 inches (915 mm) of clearance between the sides and back of the grill and any combustible surface, or use an insulating surround available from Kalamazoo.

Do not place the grill in a location where it is likely to be exposed to a strong wind.

High altitude kit available.

WARNING: This product can expose you to chemicals including nickel, which are known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warningsca.gov



K750GS Gaucho Freestanding Grill





