



810 WEST WASHINGTON BOULEVARD  
CHICAGO, IL 60607

8566 KRUM AVENUE  
GALESBURG, MI 49053

KALAMAZOOGOURMET.COM  
+1.800.868.1699

# K1000HS Hybrid Fire Freestanding Grill



<b>Overall Width / Installation Width</b>	95.25 in (2420 mm)
<b>Overall Depth / Installation Depth</b>	32 in (814 mm)
<b>Overall Height / Counter Height</b>	54.63 in (1388 mm) / 36 in (915 mm) +/- 1 ¼ in (33 mm)
<b>Approximate Product Weight</b>	750 lb (340 kg)
<b>Gas Requirements</b>	<b>Natural Gas:</b> 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick disconnect provided. Gas service line to deliver 7 i.w.c. at grill location. See BTU information below for pipe sizing.
	<b>Bulk Propane:</b> 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick disconnect provided. Gas service line to deliver 11 i.w.c. at grill location. See BTU information below for pipe sizing.
	<b>Propane Cylinder:</b> Not available
<b>Electrical Requirements</b>	120VAC/60Hz Includes 1 ft. (30.5 cm) 3-prong grounded power cord. 1.5V "AAA battery x 1 for cooktop burner ignition.
<b>Maximum AMP usage</b>	3 amps
<b>Main Burners Rating</b>	106,000 BTU liquid propane / 96,000 BTU natural gas
<b>Total BTUs</b>	181,000 BTU liquid propane / 163,500 BTU natural gas

## PRODUCT FEATURES

- 46" x 22" (1,012 square inches) of primary grilling surface
- Four cast stainless steel Dragon Burners™, 26,500 BTUs each (LP)
- Natural gas, bulk liquid propane, or 30 lb liquid propane cylinder
- Barbecue burner for indirect, low-temperature cooking
- Rotisserie system with infrared burner; motor mounted in cabinet; flip-up warming rack
- Dual cooktop burners, 20,500 BTUs each (LP)
- Safety valves for every burner and electronic control bezels with flame sensor LED indicators
- Kalamazoo's Advanced Cooking Concept with Deep hopper cleaning
- Single Hybrid Fire Grilling System Drawer
- Right end cabinet for optional propane cylinder storage
- Optional laser-cut grilling surfaces available with your choice of patterns optimized for cooking meat, fish, and vegetables
- Marine-grade stainless steel available


Ensure proper gas pipe sizing. Diameter and length of the supply pipe may limit the pressure and BTU delivery.

This appliance is certified to the ANS Z21.58/CSA 1.6 (2018) standard for Outdoor Cooking Gas Appliances. As with all appliances certified to this standard, this appliance is for outdoor use only and may not be used underneath an overhead combustible structure or surface.

Maintain at least 6 inches (153 mm) of clearance between the sides and back of the grill and any combustible surface.

High altitude kit available.

Do not place the grill in a location where the rear hood openings are likely to be exposed to strong wind. A wind break wall is recommended for installations where the prevailing wind may be a problem.



**WARNING:** This product can expose you to chemicals including nickel, which are known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warningsca.gov](http://www.P65Warningsca.gov)



810 WEST WASHINGTON BOULEVARD  
CHICAGO, IL 60607

8566 KRUM AVENUE  
GALESBURG, MI 49053

KALAMAZOOGOURMET.COM  
+1.800.868.1699

# K1000HS Hybrid Fire Freestanding Grill

