



810 WEST WASHINGTON BOULEVARD
CHICAGO, IL 60607

8566 KRUM AVENUE
GALESBURG, MI 49053

KALAMAZOOGOURMET.COM
+1.800.868.1699

K750HT Hybrid Fire Freestanding Grill



PRODUCT FEATURES

- 33" x 22" (726 square inches) of primary grilling surface
- Three cast stainless steel Dragon Burners™, 26,500 BTUs each (LP)
- Natural gas or bulk liquid propane
- Barbecue burner for indirect, low-temperature cooking
- Rotisserie system with infrared burner; motor mounted in cabinet; flip-up warming rack
- Electronic control bezels with flame sensor LED indicators
- Kalamazoo's Advanced Cooking Concept with Deep hopper cleaning
- Single Hybrid Fire Grilling System Drawer
- Two side shelves
- Optional laser-cut grilling surfaces with your choice of patterns optimized for cooking meat, fish, and vegetables
- Marine-grade stainless steel available

Overall Width / Installation Width	78.25 in (1989 mm)
Overall Depth / Installation Depth	32 in (814 mm)
Overall Height / Counter Height	54.63 in (1388 mm) / 36 in (915 mm) +/- 1 ¼ in (33 mm)
Approximate Product Weight	470 lb (213 kg)
Gas Requirements	Natural Gas: 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick disconnect provided. Gas service line to deliver 7 i.w.c. at grill location. See BTU information below for pipe sizing.
	Bulk Propane: 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick disconnect provided. Gas service line to deliver 11 i.w.c. at grill location. See BTU information below for pipe sizing.
	Propane Cylinder: Not available
Electrical Requirements	120VAC/60Hz Includes 1 ft. (30.5 cm) 3-prong grounded power cord.
Maximum AMP usage	3 amps
Main Burners Rating	79,500 BTU liquid propane / 72,000 BTU natural gas
Total BTUs	99,750 BTU liquid propane / 92,500 BTU natural gas


Ensure proper gas pipe sizing. Diameter and length of the supply pipe may limit the pressure and BTU delivery.

This appliance is certified to the ANSI Z21.58/CSA 1.6 (2018) standard for Outdoor Cooking Gas Appliances. As with all appliances certified to this standard, this appliance is for outdoor use only and may not be used underneath an overhead combustible structure or surface.

Maintain at least 6 inches (153 mm) of clearance between the sides and back of the grill and any combustible surface.

High altitude kit available.

Do not place the grill in a location where the rear hood openings are likely to be exposed to strong wind. A wind break wall is recommended for installations where the prevailing wind may be a problem.



WARNING: This product can expose you to chemicals including nickel, which are known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



810 WEST WASHINGTON BOULEVARD
CHICAGO, IL 60607

8566 KRUM AVENUE
GALESBURG, MI 49053

KALAMAZOOGOURMET.COM
+1.800.868.1699

K750HT Hybrid Fire Freestanding Grill

